



Type Designation	4720
Designation IEC	LR20
System	Zn-MnO ₂ (Alkaline)
Shelf Life (Coding)*	10 years
Nominal Voltage [V]	1.5
Typical Capacity C [mAh]	17000 (discharge with high-resistance)
Permissible Temperature Range	- 20 °C ... 50 °C
Weight, approx. [g]	140,4
Volume [ccm]	51

Dimensions [mm]	min:	max:
Ø	32.3	34.2
A	-	61.5
B	59.5	-
C	18.0	-
E	-	1.0
F	-	9.5
G	1.5	-

Typical Capacities (at 20°C):



Discharge Type	Load	End Voltage[V]	0.9
2H/D,7D/W	600 mA	Time [h]	19,2
Portable stereo		Capacity [Ah]	11,4
		Energy [Wh]	12,8
Discharge Type	Load	End Voltage[V]	0.9
4M/15M,8H/D,7D/W	2.2 Ω	Time [h]	26,6
Portable lighting		Capacity [Ah]	13,9
		Energy [Wh]	16,0
Discharge Type	Load	End Voltage[V]	0.8
1H/D,7D/W	2.2 Ω	Time [h]	27,5
Toy		Capacity [Ah]	14,4
		Energy [Wh]	16,2

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries

* In consideration of typical loss of capacity at storage and application.